

Side Mounted Hose Reels

MODEL// SR15-L350-BGX

S Series

S "Safety Series Side Mount" spring driven hose reels are compact, versatile and unique in the way they mount and operate. They feature a simple two-bolt mounting pattern for easy installation and detachment for multiple workstation applications. The 360° hose direction allows the user to operate the reel from front to back, top to bottom, any direction the job demands.

S SERIES Offers...

- ✓ 2-Bolt Mounting Pattern Easily Mounts & Detaches For Multiple Work Station Applications
- ✓ Heavy Gauge Steel Arm Mounts Flat To Any Surface Such As Tool Boxes, Benches, Vehicle Lifts, Beams, etc.
- ✓ 360° Payout Designed For Use From Any Direction
- ✓ Hose Control Bar Is Full Drum Width Preventing Derailment
- ✓ Multi-position Locking Ratchet Secures Hose At Desired Length. Non-locking, Less Ratchet Option Available (Add Suffix -BXC)



Right hand model shown

- Drive Type** Spring
- Media**
- Air
 - Water
 - Oil
 - Grease
- Swivel material** Brass
- Seal material** Nitrile



LOW PRESSURE // Air & Water

RIGHT MODELS hose	LEFT MODELS hose	RIGHT MODELS no hose	LEFT MODELS no hose	I.D. mm	O.D. mm	Length	BAR	Inlet	Outlet	KG hose	KG no hose	Size
SR13-L125-BGX	SL13-L125-BGX	SR13L-L125-BGX	SL13L-L125-BGX	6	12	8 m	21	1/4"	1/4"	8	6	1
SR15-L135-BGX	SL15-L135-BGX	SR15L-L135-BGX	SL15L-L135-BGX	6	12	11 m	21	1/4"	1/4"	10	8	2
SR15-L325-BGX	SL15-L325-BGX	SR15L-L325-BGX	SL15L-L325-BGX	10	17	8 m	21	3/8"	3/8"	10	8	2
SR17-L350-BGX	SL17-L350-BGX	SR17L-L350-BGX	SL17L-L350-BGX	10	17	15 m	21	3/8"	3/8"	15	11	3
SR17-L430-BGX	SL17-L430-BGX	SR17L-L430-BGX	SL17L-L430-BGX	12	21	9 m	21	1/2"	1/2"	15	13	3
SR19-L450-BGX	SL19-L450-BGX	SR19L-L450-BGX	SL19L-L450-BGX	12	21	15 m	21	1/2"	1/2"	17	13	5

Maximum temp. 65°C Reels without hose can be used for air, water & oil

MEDIUM PRESSURE // Air, Water & Oil

RIGHT MODELS hose	LEFT MODELS hose	RIGHT MODELS no hose	LEFT MODELS no hose	I.D. mm	O.D. mm	Length	BAR	Inlet	Outlet	KG hose	KG no hose	Size
SR17-M325-BGX	SL17-M325-BGX	SR17L-M325-BGX	SL17L-M325-BGX	10	17	8 m	210	3/8"	3/8"	19	15	3
SR17-M425-BGX	SL17-M425-BGX	SR17L-M425-BGX	SL17L-M425-BGX	12	21	8 m	175	1/2"	1/2"	17	14	3
SR19-M350-BGX	SL19-M350-BGX	SR19L-M350-BGX	SL19L-M350-BGX	10	17	15 m	210	3/8"	3/8"	22	16	5
SR19-M450-BGX	SL19-M450-BGX	SR19L-M450-BGX	SL19L-M450-BGX	12	21	15 m	175	1/2"	1/2"	23	16	5

Reels with hose come with one wire braid hose suitable for air, water & oil with a maximum temp. 99°C


DIMENSIONS

SIZE	A	B	C	D
1	330	152	362	235
2	387	152	419	260
3	432	146	464	330
4	432	165	464	330
5	483	197	521	378
6	483	216	521	378

HIGH PRESSURE // Air, Water, Oil & Grease

RIGHT MODELS hose	LEFT MODELS hose	RIGHT MODELS no hose	LEFT MODELS no hose	I.D. mm	O.D. mm	Length	BAR	Inlet	Outlet	KG hose	KG no hose	Size
SR17-H125-BGX	SL17-H125-BGX	SR17L-H125-BGX	SL17L-H125-BGX	6	12	8 m	350	1/4"	1/4"	17	14	4
SR17-H325-BGX	SL17-H325-BGX	SR17L-H325-BGX	SL17L-H325-BGX	10	17	8 m	280	3/8"	3/8"	17	14	4
SR19-H150-BGX	SL19-H150-BGX	SR19L-H150-BGX	SL19L-H150-BGX	6	12	15 m	350	1/4"	1/4"	21	16	6
SR19-H350-BGX	SL19-H350-BGX	SR19L-H350-BGX	SL19L-H350-BGX	10	17	15 m	280	3/8"	3/8"	22	16	6

Maximum temp. 99°C



MOUNTING BRACKETS

MODELS	For models
15726-13	SR13 & SL13
15726-15	SR15 & SL15
15726-17	SR17 & SL17
15726-19	SR19 & SL19

MODELS	For models
SMB1	SR13, SL13, SR15 & SL15
SMB2	SR17 & SL17
SMB3	SR19 & SL19



360° Payout



Multiple Applications

